

**TECHNICAL INFORMATION SHEET****PVC Clear Cut Edge Sealant LVOC****Item Description**

16 oz. (0.47 L) squeeze bottles  
with applicator nozzles

**Item Number**

W56PAC2001

**Product Information****Description:**

Firestone PVC Clear Cut Edge Sealant LVOC is an optional treatment used for sealing cut edges of PVC membrane where scrim reinforcement is exposed.

**Method of Application:**

1. Surfaces to receive PVC Clear Cut Edge Sealant LVOC must be clean, dry, and free of loose and foreign materials, oil and grease.
2. Allow the welded seam to cool prior to application of PVC Cut Edge Sealant LVOC. Seam should be cool to the touch.
3. Clean seam area with Firestone Splice Wash SW-100 prior to treating the cut edge with sealant.
4. Trim the tip of the nozzle to provide approximately a  $\frac{1}{8}$ " (3.2 mm) opening.
5. Apply an approximate  $\frac{1}{8}$ " to  $\frac{1}{4}$ " (3.2 mm to 6.4 mm) diameter bead of sealant to cut edges of Firestone PVC membrane with exposed reinforcement.

**Storage:**

Shelf life of one year can be expected if stored in original sealed container at temperatures between 60 - 80 °F (16 - 27 °C) in a cool, well-ventilated area. Shelf life will be shortened if exposed to elevated temperatures.

**Coverage Rate:**

- $\frac{1}{8}$ " (3.2 mm) diameter bead: 1,500 ft/gal (121 m/L)
- $\frac{1}{4}$ " (6.4 mm) diameter bead: 400 ft/gal (32 m/L)

**Precautions:**

- Review Safety Data Sheet (SDS) prior to use.
- Flammable. Keep away from fire and open flame and other possible ignition sources during storage and use. Do not smoke when using.
- Harmful or fatal if swallowed.
- Avoid prolonged inhalation.
- Avoid prolonged contact with skin. Gloves should be worn (OSHA approved).
- Avoid eye contact by wearing safety goggles with side shields.
- Thinning is not allowed.
- Do not use for splicing.
- Use only in well ventilated areas.
- Cover tightly when not in use.

**LEED® Information:**

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Akron, OH

\*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.



**TECHNICAL INFORMATION SHEET****PVC Clear Cut Edge Sealant LVOC****Typical Properties**

<u>Property</u>	<u>Typical Performance</u>
Color	Clear
Solvents	Parachlorobenzotriflouride (PCBTF), Methyl isobutyl ketone (MIBK)
Percent Solids	21% - 24%
Viscosity	4000 - 7000 cPs #3 spindle @ 10 rpm at Room Temperature
Specific Gravity	10.35 – 10.55 lb (4.69 – 4.79 kg)
V.O.C. Content	190 g/L

**Product Packaging**

Bottle	Pint
Carton	12 pints/ carton
Weight per Carton	18 lb (8.2 kg)

Please contact Firestone Technical Services at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.