

TECHNICAL INFORMATION SHEET

PVC Universal Pipe Flashing



Item Description

White

Item Number

W56PAW1006

Product Information

Description:

Firestone PVC Universal Pipe Flashing is specifically designed for the flashing of round penetrations. PVC Universal Pipe Flashing fits various penetrations from 1" (25 mm) to 4½" (114.3 mm). The Firestone PVC Universal Pipe Flashing must be cut to correct size before installation.

Method of Application:

1. Firestone PVC membrane shall be clear of all dust, dirt and other contaminants prior to installation of the Firestone PVC Universal Pipe Flashing.
2. Penetration shall be clean of foreign material and any old flashing materials.
3. Cut out a circle, above the rib, on the outside of a level ring of the Firestone PVC Universal Pipe Flashing that is smaller than the penetration.
4. Heat-weld the flashing into place and install the clamp and Firestone All Purpose Sealant per current Firestone PVC specifications.

Storage:

Store material in its original unopened packaging away from sources of physical damage or chemical contamination.

Precautions:

Do not install over uneven substrates.

LEED® Information:

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Hillside, NJ

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

Typical Properties

Property	Value
Material	PVC with DuPont Elvaloy® KEE
Color	White
Clamp	Stainless steel – worm gear type
Pipe Flange	10¾" (273 mm) diameter
Thickness	0.085" (2.16 mm) ± 10%
Pipe height	7" (178 mm)
Clamp	Stainless steel, worm gear type

Fits the Pipe Outside Diameter

1"	25 mm
1½"	38 mm
2"	50 mm
3"	76 mm
4"	102 mm
4½"	114 mm

Product Packaging

Units per Carton	10 Firestone PVC Universal Pipe Flashings - 10 SS Clamps
------------------	--

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.